

IBM

Exam 000-784

IBM PureFlex Technical Expert V1

Version: 6.0

[Total Questions: 70]

Question No : 1

A client has purchased a Flex System with a Flex System Manager (FSM) and a p260 node. Which of the following is the most cost-effective procedure to install the VIO server?

- A. Engage Lab Services to complete the installation
- B. Use the external USB DVD RAM that IBM delivers with a Flex System
- C. Copy the VIO ISO images onto the FSM and use the installios command
- D. Launch the Remote Control from the FSM and remote mount the VIO ISO images from your workstation

Answer: C

Question No : 2

A client requires the following management functions of their PureFlex environment:

Secure boot: TPM and CRTM
Signed firmware updates to ensure authenticity
Chassis and compute node detection and provisioning
Security policy management
Discover network devices in your environment
Monitor the health and status of network devices
Manage devices by groups:
Ethernet switches, Fibre Channel over Ethernet, or Subnet Discovery of physical and virtual storage devices
Support for virtual images on local storage across multiple chassis
Inventory of physical storage configuration
Storage pool configuration
Disk sparing and redundancy management
Virtual volume management
Support for virtual volume discovery, inventory, creation, modification, and deletion

Which management function is used to execute these tasks?

- A. IBM PowerSC
- B. IBM SmartCloud Entry
- C. IBM Flex System Manager
- D. IBM Chassis Management Module

Answer: C

Question No : 3

A client has a PureFlex system and needs to upgrade their Flex System V7000 Storage

Node. Which interface would be used to accomplish this?

- A. FSM
- B. BIOS upgrade
- C. Chassis Manager
- D. Flex Node Interface GUI

Answer: A

Question No : 4

The client seeks to reduce cost and complexity in a highly virtualized x86 environment. They want the network policies to migrate automatically along with mobile virtual machines to ensure that security, performance and access remains intact as virtual machines move from server to server. VMware is their virtualization standard. Which option will provide a complete solution?

- A. Switches capable to support 802.1 QBG
- B. Cisco Nexus 1000V on IBM VMready Switches
- C. IBM Switch-resident IBM VMready capability
- D. IBM Software Defined Networking (SDN) for Virtual

Answer: D

Question No : 5

IBM 000-784 : Practice Test

A Managed Service Provider (MSP) is looking for a platform on which to base their rapidly growing offerings. Their offerings include pre-packaged solutions for virtual computing, virtual desktop, virtual storage, general application support, and IaaS. They distinguish themselves with the ease of use of their user portal and services catalog, as well as offering a variety of service level agreements. Customers include gaming, financial, retail, health industries, government, telecommunications, and application developers.

The organization has a very strong technical skill base with an in-house development culture.

Key decision criteria includes rapid automated provisioning, multi-tenancy, isolation, security, billing and metering based on allocation and usage, and pay-as-you-grow scalability. High availability and disaster recovery are essential. They have a strong interest in KVM and Open Source to minimize cost, and exploit their core skills.

The current networking infrastructure is based upon Juniper switches and security devices.

They are currently considering IBM PureSystems and VCE Vblock, as well as non-integrated alternatives.

A client wants to provide a Flex solution that compares to a standard Power 750 running PowerVM and AIX. The client asks for a Flex System compute node with similar capacity and scalability for processor and memory. Which node should be discussed with the prospect?

- A. Flex node p270
- B. Flex node p24L
- C. Flex node p260
- D. Flex node p460

Answer: D

Question No : 6

A client has a need for a Linux based solution that requires a large amount of memory. The application runs on either x86 or Power nodes. Which of the following nodes would provide the maximum memory configuration?

- A. p460
- B. x440
- C. p24L
- D. x240

Answer: B

Question No : 7

A client has a number of Power servers that are virtualized and boot from FC SAN with dual VIO servers. The client is considering consolidation of server and network hardware (LAN and SAN) while maximizing the return on investment by leveraging existing shared FC storage. Which option meets the client requirements?

- A. Utilize FCoE to boot the VIO servers
- B. Utilize iSCSI to boot the VIO servers
- C. Continue to use FC SAN for the VIO servers
- D. Use a pair of internal drives to provide for the VIO servers

Answer: A

Question No : 8

The IBM Flex System Interoperability Guide is a handy reference document but its information is only as accurate as of its most recent publication date. Where would the technical expert find the latest complete information on supported FCoE configurations?

- A. The FC-BB-5 standards documentation
- B. IBM Flex System product development
- C. Reference IBM's ServerProven web page
- D. IBM System Storage Interoperation Center (SSIC)

Answer: D

Question No : 9

A client wants to see how the 900 GB 10k drives would be used in a RAID 5 set to migrate their 30 TB of storage. Which tool can the technical expert use to show the layout for Flex System V7000 Storage Node?

- A. Disk Magic
- B. Capacity Magic
- C. TCOnow! for Disk

D. IBM Flex System TCO Analysis**Answer: B****Question No : 10**

A client wants a PureFlex Express configuration with an additional EN4093R 10Gb Scalable Switch module for redundancy. The Power nodes in the configuration have four-port 10Gb NICs and the client applications planned for the Power nodes will require the use of all four of those ports. What must the technical expert include in the configuration to meet this requirement?

- A. An additional pair of EN4093R 10Gb Scalable Switch modules
- B. IBM Flex System CN4054 Virtual Fabric Adapter Upgrade for each CN4054 adapter
- C. IBM Flex System Fabric EN4093 10Gb Scalable Switch (Upgrade 1) for each switch
- D. IBM Flex System Fabric EN4093 10Gb Scalable Switch (Upgrade 2) for each switch

Answer: C**Question No : 11**

A large enterprise client wants to perform a benchmark on a PureFlex System to compare the performance against a competitive solution. What is the best way for the client to proceed?

- A. Try and Buy a PureFlex System and let the client perform the benchmark
- B. Lease a PureFlex System from a Business Partner and have the Partner perform the benchmark
- C. Invite the client to the local IBM Client Center (ICC) and have the ICC perform the benchmark
- D. Visit an IBM Products and Solutions Support Center (PSSC) and have the PSSC perform the benchmark

Answer: D**Question No : 12**

Exhibit:

IBM 000-784 : Practice Test

A small manufacturing company is interested in a platform to support their new SAP CRM deployment. Currently installed systems include IBM BladeCenter, HP BladeSystem, and standalone servers from various vendors. They have standardized on the use of VMware on x86, and are 70% virtualized. There are no Power Systems servers currently installed.

They are very pleased with their IBM XIV storage, particularly the simplicity, and continue to expand with additional XIV Gen3 capacity when required.

The current data center network is based on Cisco Catalyst 1Gb switches at the edge with Cisco Nexus 5596 10Gb core switches. They also have a legacy Brocade SAN. For systems management, they use vendor-specific element management tools.

They have two sites: a main site and a secondary site, and they currently have limited high availability capabilities. They have decided they are not interested in hosted Cloud services at this time.

They have a small staff, so ease-of-use and simplification are particularly important. The Cisco sales team has convinced them that FCoE is easier; consequently, FCoE is very attractive to them.

They typically focus on the tactical administration and day-to-day activities. Decision making is driven largely by technical staff. In addition to IBM PureSystems, they are considering Cisco UCS.

In order to support the client's requirement for FCoE with the 10Gb Virtual Fabric Ethernet LAN-on-motherboard (LOM) which optional feature must be included?

- A. A second CPU that matches the first one installed
- B. IBM Flex System Embedded 10Gb Virtual Fabric Upgrade
- C. IBM Flex System Fabric EN4093 10Gb Scalable Switch (Upgrade 1)
- D. IBM Flex System Fabric CN4093 Converged Scalable Switch (Upgrade 2)

Answer: B

Question No : 13

Exhibit: