

SCO

Exam 090-078

UNIXWARE 7 ACE FOR MASTER ACE V10A1

Version: 5.0

[Total Questions: 80]

Topic 0, A

A

Question No : 1 - (Topic 0)

What is the default filesystem type used to create a filesystem in UnixWare 7?

- A. AFS (Acer Fast Filesystem)
- B. vxfs (Veritas Filesystem)
- C. S5 (System V Filesystem)
- D. UFS (Extended S5 Filesystem)

Answer: B**Question No : 2 - (Topic 0)**

Which command clears the contents of the /var/adm/syslog file without deleting the file itself?

- A. > /var/adm/syslog
- B. < /var/adm/syslog
- C. rm /var/adm/syslog
- D. clear /var/adm/syslog

Answer: A**Question No : 3 - (Topic 0)**

Which system process is the ancestor of all user processes?

- A. ifor_pmd(1M)
- B. init(1M)
- C. syslogd(1M)
- D. sysproc(1M)

Answer: B**Question No : 4 - (Topic 0)**

What is the maximum vxfs (VERITAS) filesystem size?

- A. 2 terabytes
- B. 1 terabyte
- C. 2 gigabytes
- D. 1 gigabyte

Answer: B

Question No : 5 - (Topic 0)

How many partitions can you define on the first hard disk during the installation of the UnixWare 7 operating system?

- A. One (1)
- B. Two (2)
- C. Three (3)
- D. Four (4)

Answer: D

Question No : 6 - (Topic 0)

Which command do you use to create a set of emergency floppy diskettes?

- A. diskadd(1M)
- B. disksetup(1M)
- C. emergency_disk(1M)
- D. emergency_rec(1M)

Answer: C

Question No : 7 - (Topic 0)

Which statement is false?

- A. The vxfs filesystem supports the creation of 2 terabyte file sizes by default.
- B. The vxfs filesystem supports the creation of up to 2 gigabyte file sizes by default.
- C. The vxfs filesystem supports a 4 kilobyte logical block size.
- D. The vxfs filesystem supports an 8 kilobyte logical block size.

Answer: A

Question No : 8 - (Topic 0)

Which answer describes the correct order in which diskadd(1M) invokes commands to configure additional disks?

- A. fdisk(1M), mkfs(1M), and disksetup(1M)
- B. disksetup(1M), fdisk(1M), and mkfs(1M)
- C. fdisk(1M), disksetup(1M), and mkfs(1M)
- D. None of the above.

Answer: C

Question No : 9 - (Topic 0)

If it exists, in which hard disk slice is the PDINFO (Physical Disk Information) stored?

- A. The boot slice
- B. The dump slice
- C. The var slice
- D. The volume management public slice

Answer: C

Question No : 10 - (Topic 0)

How many hard disk slices are created by default?

- A. 16
- B. 32
- C. 64
- D. 128

Answer: A

Question No : 11 - (Topic 0)

How many detected hard disks can you create partitions and filesystems on during the installation of the UnixWare 7 operating system?

- A. Eight (8)
- B. Six (6)
- C. Four (4)
- D. Two (2)

Answer: D

Question No : 12 - (Topic 0)

Which of the following can you NOT use the Boot Command Processor (BCP) to accomplish?

- A. Display or change default boot parameters
- B. Enter single-user state
- C. Load another UNIX kernel
- D. Start the print service

Answer: D

Question No : 13 - (Topic 0)

Which command would you use to view the options that were used to create an existing hard disk filesystem?

- A. mkfs /dev/rdisk/c0b0t0d0s4
- B. mkfs -m /dev/rdisk/c0b0t0d0s4
- C. prtvtoc /dev/rdisk/c0b0t0d0s4
- D. prtvtoc -p /dev/rdisk/c0b0t0d0s4

Answer: A

Question No : 14 - (Topic 0)

Which kernel parameter controls the maximum number of processes that a user can run at any given time?

- A. MAX_PROC