

117-303

117-303

LPI Level 3 Exam (LPI 303: Security)

Version 3.1

117-303

QUESTION NO: 1

An administrator has just configured an OpenVPN client. Upon starting the service, the following message is displayed:

TLS Error: TLS key negotiation failed to occur within 60 seconds

Which of the following statements is true?

- A. The client was unable to establish a network connection with the server.
- B. The client was able to establish a network connection with the server, however TLS key negotiation failed, resulting in a fallback to SSL.
- C. The client was able to establish a network connection with the server, however TLS and SSL security are not enabled.
- D. The client was able to establish a network connection with the server, however TLS key negotiation took longer than 60 seconds, indicating that there may be a problem with network performance.

Answer: A

QUESTION NO: 2

SELinux has just been installed on a Linux system and the administrator wants to use SELinux in permissive mode in order to audit the various services on the system. What command will switch SELinux into permissive mode?

- A. setenforce 0
- B. /etc/init.d/selinux stop
- C. selinux passive
- D. /etc/init.d/selinux startpassive

Answer: A

117-303

QUESTION NO: 3

Which of the following export options, when specified in /etc/exports, will tell the server to use the NFSv4 Pseudofilesystem?

- A. fsid=2
- B. fsid=0
- C. fsid=3
- D. fsid=1

Answer: B

QUESTION NO: 4

Which of the following are common techniques for securing a sendmail server? (Select THREE correct answers)

- A. Maintain user accounts in an LDAP directory.
- B. Enable TLS.
- C. Disable VRFY.
- D. Run sendmail in a chroot'd environment.
- E. Disable USRLKUP.

Answer: B, C, D

QUESTION NO: 5

What does ntop use for data collection?

117-303

- A. Network packets
- B. Log files
- C. Frame relay
- D. SNMP

Answer: A

QUESTION NO: 6

An administrator has successfully configured a cryptographic volume for dmccrypt, and has added the following line to /etc/fstab:

```
/dev/mapper/cryptvol /media/crypt auto defaults 0 0
```

Upon booting the system, the error message "mount: special device /dev/mapper/cryptvol does not exist" is displayed. What configuration file has the administrator forgotten to edit? (Provide the full path and filename)

Answer: /etc/crypttab

QUESTION NO: 7

What command will remove the dmccrypt mapping named cryptvol? (Provide the command with any options and parameters)

Answer: /sbin/cryptsetup remove crypt-vol cryptsetup remove crypt-vol

QUESTION NO: 8

Which LUKS action, when supplied to the cryptsetup command, will initialize a LUKS partition and set the initial key? (Provide only the action name)

Answer: luksFormat

117-303

QUESTION NO: 9

An administrator has created a mapping with the following command:
cryptsetup luksOpen /dev/sda1 cryptvol and has set three different keys. Which command below will delete the first key?

- A. cryptsetup luksDelKey /dev/sda1 0
- B. cryptsetup luksDelKey /dev/sda1 1
- C. cryptsetup luksDelKey /dev/mapper/cryptvol 1
- D. cryptsetup luksDelKey /dev/mapper/cryptvol 0

Answer: A

QUESTION NO: 10

What command will list basic information about all targets available to cryptmount? (Provide the command with any options or parameters)

Answer: cryptmount

--list

/usr/bin/cryptmount

-l

/usr/bin/cryptmount

--list cryptmount -l

QUESTION NO: 11

Which of the following are valid dmccrypt modes? (Choose THREE correct answers)

117-303

- A. XTS
- B. ESSIV
- C. GMR
- D. KWG
- E. LRW

Answer: A, B, E

QUESTION NO: 12

Which directive in the OpenVPN client.conf specifies the remote server and port that the client should connect to? (Provide only the directive, without any options or parameters)

Answer: remote

QUESTION NO: 13

You are certain that your kernel has been compiled with ACL support, however, when you try to set an ACL on a file, you get the following output:

```
% setfacl m user:hugh:r afile.txt
```

```
setfacl: afile.txt: Operation not supported
```

What is the most likely reason for this problem?

- A. There is an error in the command line parameters.
- B. There is no user on the system named hugh.
- C. The partition has not been mounted with the acl option.
- D. The file afile.txt doesn't exist.

117-303

Answer: C

QUESTION NO: 14

Which of the following are valid OpenVPN authentication modes? (Choose TWO correct answers)

- A. S/Key
- B. Kerberos
- C. Static Key
- D. Password
- E. TLS

Answer: C, E

QUESTION NO: 15

What is true about the permissions for the file afile given the following output from getfacl?
(Select TWO correct answers)

```
% getfacl afile  
  
# file: afile  
  
# owner: matt  
  
# group: support  
  
user::rwx  
  
user:hugh:rw  
  
group::r  
  
group:staff:rx  
  
mask::rwx
```

117-303

other::r

- A. Anyone in the support group will be able to read and execute the file.
- B. The user hugh will be able to read the contents of the file.
- C. Anyone in the users group will be able to read the file.
- D. The user matt will not be able to edit this file.
- E. Anyone in the staff group will be able to read and execute the file.

Answer: B, E

QUESTION NO: 16

You wish to revoke write access for all groups and named users on a file. Which command will make the correct ACL changes?

- A. setfacl x group:*:rx,user:*:rx afile
- B. setfacl x mask::rx afile
- C. setfacl m mask::rx afile
- D. setfacl m group:*:rx,user:*:rx afile

Answer: C

QUESTION NO: 17

What is the default UDP port for OpenVPN traffic?

Answer: 1194