

# IBM

## Exam C4040-108

### Enterprise Technical Support for AIX and Linux -v2

Version: 6.6

[ Total Questions: 130 ]

**Question No : 1**

Which power reduction technology requires a software component in order to be activated?

- A. Power capping
- B. Processor folding
- C. Static power saving
- D. Processor core nap mode

**Answer: A**

**Question No : 2**

Which of the following commands will enable the SEA accounting?

- A. chacct -dev ent14 -attr enable
- B. optimizenet -setaccounting=enabled
- C. chsea -dev ent14 -attr accounting=enable
- D. chdev -dev ent14 -attr accounting=enabled

**Answer: D**

**Question No : 3**

A customer backs up a database using tools provided by the vendor. The backup files are written to a filesystem that was initially created for use by the database, but the backup takes an unexpectedly long time. Which of the following methods will decrease the time required for backups?

- A. Use the vmo command to increase WriteBehind.
- B. Switch on Concurrent I/O for target filesystems.
- C. Switch off Concurrent I/O for target filesystems.
- D. Use the backup tools provided with the operating system.

**Answer: C**

**Question No : 4**

A company which sells books and DVDs runs their business on AIX Enterprise Edition on a Power 795. They have LPARs running back-office applications and other LPARs supporting their Internet based retail operations. They are considering a policy of switching between TurboCore mode and MaxCore mode, depending on workload. Which of the following considerations will have the most impact on the customer's business?

- A. The managed system will need to be restarted to change modes.
- B. There will be fewer cores available when using TurboCore mode.
- C. There will be less L3 cache available per core when using MaxCore mode.
- D. The applications running on the affected LPARs must support MaxCore and TurboCore modes.

**Answer: A**

**Question No : 5**

A customer has an existing deployment of IBM i LPARs running on POWER6 hardware. The customer is planning to add new AIX and IBM i LPARs on the same hardware. To avoid purchasing additional adapters, there is a requirement for the new LPARs to be completely virtualized. What virtualization options exist for hosting IBM i and AIX LPARs?

- A. Virtualization Engine (VE)
- B. N\_Port ID Virtualization (NPIV)
- C. Advanced Power Virtualization (APV)
- D. Network Server Description (NWSD) and VIO Server

**Answer: D**

**Question No : 6**

Which of the following commands traces a processes system calls, received signals, and machinefaults?

- A. prof
- B. topas
- C. truss
- D. mpstat

**Answer: C**

**Question No : 7**

A system administrator must provide network access to a single VLAN for multiple partitions on a Power 795 server. The Power 795 server has a pair VIO Server (VIOS) partitions, with a Shared Ethernet Adapter (SEA) in each one. Each SEA will use a single-port Ethernet adapter as a backing device. Both SEAs must support network traffic so both adapters are used simultaneously. Network service must be resilient. All client partitions must be able to maintain network access to this VLAN through either VIOS partition if the other VIOS partition fails or is taken out of service. Which of the following configurations would satisfy this goal?

- A.** The SEAs are both connected to the same virtual switch. Both SEAs are configured for SEA failover. The client LPARs are configured with one virtual Ethernet adapter
- B.** The SEAs are each connected to separate virtual switches. Both SEAs are configured for SEA failover. The client LPARs are configured with one virtual Ethernet adapter.
- C.** The SEAs are both connected to the same virtual switch. Neither SEA is configured for SEA failover. The client LPARs are configured with NIB on two virtual Ethernet adapters.
- D.** The SEAs are each connected to separate virtual switches. Neither SEA is configured for SEA failover. The client LPARs are configured with NIB on two virtual Ethernet adapters.

**Answer: D**

**Question No : 8**

An administrator attempts to migrate a running LPAR using the 'migr\_lpar' command. :

The command fails with two errors:  
[VIOSE01090002-0445] The destination system is not compatible with the migrating partition.  
[VIOSE01090024-0605] Partition with ID 2 cannot be migrated because the destination managed system does not support the desired processor compatibility mode.

What task will help the administrator determine the cause of the errors?

- A.** Validate the configured attributes on the Properties tab of the LPAR profile.
- B.** Validate that the VIO servers have the Mover Service Partition (MSP) attributes set.
- C.** Validate that the required CPU entitlements are available on the destination server.
- D.** Validate that the Logical Memory Block (LMB) size is consistent between both source and destination.

**Answer: B**

**Question No : 9**

An administrator who manages systems in a remote 'lights-out' data center has been sent a set of AIX device drivers for some storage arrays. The software was sent by email from the third party manufacturer, in the form of an ISO image. What is the quickest and easiest way to install the drivers?

- A. Using a PC, open a browser window onto the HMC 'updates' page Select the ISO file on the PC and follow the on-screen instructions
- B. Write the ISO image to a CD and place it in a drive on the server Follow the manufacturer's documentation to complete the installation
- C. Transfer the ISO image to a temporary directory on the AIX system cd into the directory and run 'inutoc' followed by 'smitty installp'
- D. Copy the ISO image to AIX and mount it using the 'loopmount' command Install from the mounted filesystem using the third party guidelines

**Answer: C**

**Question No : 10**

All Power 795 system racks must have door assemblies installed. Three distinct door styles are available. One of the options - the acoustical door kit - reduces the noiseemissions from the system. What attributes are improved by the other 2 door styles?

- A. Weight, height
- B. Depth, security
- C. Depth, temperature
- D. Height, temperature

**Answer: C**

**Question No : 11**

After upgrading their HMCs to the V7R720 release, a customer was planning to consolidate HMCs by taking advantage of the raised limit for maximum managed LPARs. They have

found two POWER6 570s on which the password for both HMC and admin UserIDs has been forgotten. What ASMI UserID can the customer use, when directed by IBM Support, to reset the forgotten passwords?

- A. ibm
- B. root
- C. padmin
- D. celogin

**Answer: D**

**Question No : 12**

A client is running a two node active/passive cluster on AIX 6.1 and needs to migrate AIX versions while minimizing the time the cluster runs without a failover node available. They plan to migrate the passive node, before moving the resources off the active node to migrate it. Which of the following options will minimize the time that the passive node is unavailable?

- A. Run a network-boot NIM migration from the NIM master on the current passive node.
- B. Run a local migration from assigned a DVD-RAM media to remove any network overheads.
- C. Run the migration using nimadm with cluster services still running on the passive node.
- D. Run alt\_disk\_copy to create a backup to a spare disk prior to initiating a NIM migration.

**Answer: C**

**Question No : 13**

A partition is running on a Power 770 using POWER7 mode and SMT4. The LPAR has 8.0 units of entitled capacity assigned, and has 10 virtual processors configured. If the customer uses nmon to monitor processor activity, how many processors will be shown on the summary screen?

- A. 8
- B. 10
- C. 32
- D. 40

Answer: D

**Question No : 14**

In the following topas output, what does '%client' mean?

```

Topas Monitor for host: purple1
Tue Nov 30 21:30:11 2010 Interval: 2

CPU User% Kern% Wait% Idle% Physc Entc
ALL 0.2 2.7 14.5 82.7 0.10 4.8

Network KBPS I-Pack O-Pack KB-In KB-Out
Total 2.3 10.0 7.0 0.9 1.4

Disk Busy% KBPS TPS KB-Read KB-Writ
Total 100.0 94.1K 2082.0 94.1K 0.0

FileSystem KBPS TPS KB-Read KB-Writ
Total 23.8K 2.6K 23.8K 0.0

Name PID CPU% PgSp Owner
tar 5374164 1.8 2.0 root
topas 5505054 1.2 1.8 root
vmmd 458770 0.5 1.2 root
syncd 1245610 0.1 0.6 root
java 3604698 0.0 43.6 root
getty 4587734 0.0 0.6 root
swapper 264 0.0 0.4 root
gil 459100 0.0 0.9 root
java 1966552 0.0 37.2 pconsole

EVENTS/QUEUES FILE/TTY
Cswitch 891 Readch 23.8M
Syscall 6674 Writech 23.9M
Reads 2799 Rawin 0
Writes 2454 Ttyout 815
Forks 0 Igets 0
Execs 0 Namei 600
Runqueue 0.0 Dirblk 0
Waitqueue 1.0

PAGING
Faults 459
Steals 0
PgspIn 0
PgspOut 0
PageIn 6169
PageOut 0
Sios 6169

MEMORY
Real,MB 4096
% Comp 33
% Noncomp 34
% Client 34

PAGING SPACE
Size,MB 512
% Used 2
% Free 98

NFS (calls/sec)
SerV2 0 WPAR Activ 0
CliV2 0 WPAR Total 0
SerV3 0 Press: "h"-help
CliV3 0 "q"-quit
    
```

- A. Percentage of memory that can be paged to paging space.
- B. Percentage of real memory used by non-kernel processes.
- C. Percentage of virtual memory currently allocated to cache JFS2 files.
- D. Percentage of real memory currently allocated to cache JFS2 and NFS files.

Answer: D

**Question No : 15**

Which was the first release of IBM i to support Multipath I/O (MPIO) at the client LPAR level, when the same storage is served from redundant VIO Servers?

- A. 6.1.0

- B. 6.1.1
- C. 7.1.0
- D. 7.1.1

**Answer: A**

**Question No : 16**

A customer has a Power 770 and a Power 795 managed by a single HMC. The existing HMC has two network connections.

The first adapter is connected to the general company network and uses a static IP address. The second adapter is connected to a network switch which also has connections to the Flexible Service Processors (FSPs) of the managed systems and acts as a DHCP server.

It has been decided to add a second HMC for resilience.

Which of the following is a supported method of configuring the new HMC, in relation to the existing HMC?

- A. On the same public network On the same private network, using a different DHCP range
- B. On a different public network On the same private network, using the same DHCP range
- C. On the same public network On a different private network, using the same DHCP range
- D. On a different public network On a different private network, using a different DHCP range

**Answer: D**

**Question No : 17**

A customer is upgrading a Power 595 to a Power 795 and wants to know the estimated power usage of the upgraded system. What is the most comprehensive source for this information?

- A. Facts and Features
- B. Workload Estimator
- C. System Energy Estimator
- D. Server Specification Sheets

**Answer: C**



**Question No : 18**

A customer is adding a second HMC to their two-enclosure Power 780 to provide redundancy. Which of the following is required?

- A. Each HMC requires different DHCP address ranges.
- B. The HMCs must be connected to the same FSP port in different enclosures.
- C. Both HMCs must be connected to the managed systems on the same private subnet.
- D. The primary HMC must be configured as a DHCP host and the failover HMC must be a DHCP client.

**Answer: A**

**Question No : 19**

A customer wants to consolidate 5 System p servers to a Power 780. Each of the 5 systems run as a single LPAR. Three systems run applications which are certified by the vendor for AIX 5.2 only. One system runs AIX 5.3, and the last one runs AIX 6.1. Which of the following is a supported configuration for consolidation?

- A. Create three AIX 5.2 LPARs, one AIX 5.3 LPAR, and one AIX 6.1 LPAR.
- B. Create one AIX 7.1 LPAR hosting three AIX 5.2 WPARs, one AIX 5.3 LPAR, and one AIX 6.1 LPAR.
- C. Create one AIX 7.1 LPAR hosting three AIX 5.2 WPARs, one AIX 5.3 WPAR, and one AIX 6.1 WPAR.
- D. Create one AIX 7.1 LPAR hosting three AIX 5.2 WPARs, and one AIX 6.1 LPAR hosting one AIX 5.3 WPAR.

**Answer: B**

**Question No : 20**

A system administrator would like to add a new LPAR to an existing Power 770 system that currently hosts 4 other LPARs. The system has a total of 52 GB of RAM installed and is licensed for Active Memory Expansion (AME). The current LPARs each have 12 GB of RAM allocated to them, and are tolerant of varied response times. The new LPAR

requires 8 GB of RAM, and requires consistent response time. There is no money available to purchase additional RAM. Which of the following options will support adding the new LPAR to the system with minimal impact to the existing partitions?

- A. For each of the pre-existing LPARs, configure AME. For the new LPAR, do not activate AME, and assign 8 GB of RAM.
- B. For each of the pre-existing LPARs, do not activate AME. For the new LPAR, configure AME, and assign 4 GB of RAM.
- C. For each of the pre-existing LPARs, activate and employ AME. For the new LPAR, configure AME, and assign 4 GB of RAM.
- D. For each of the pre-existing LPARs, configure AME, and reduce the physical RAM allocated. For the new LPAR, do not activate AME, and assign 8 GB of RAM.

**Answer: D**

**Question No : 21**

A customer needs to verify the resources allocated to an AIX 6.1 LPAR. The Operator Panel on the front of the physical system indicates it is managed by an HMC, however the customer is unaware of exactly which HMC. To avoid the customer logging on to 25 HMCs, which AIX command can be used to query the IP address of the managing HMC?

- A. `lssrc -ls ctrmc`
- B. `grep -ri hmc /var/ct/`
- C. `lssrc IBM.ManagementServer`
- D. HMC hostname is listed within `/etc/hosts`

**Answer: C**

**Question No : 22**

While restoring a mksysb to a VIO client, the installation halts with a message indicating lack of space. The mksysb being used for the restore is 4GB in size. The client LPAR has an assigned 32GB LUN through the VIO Server. What is wrong?

- A. The extracted files plus required temporary working storage exceeds 32GB.
- B. The logical volumes defined in `image.data`, together require more than 32 GB.
- C. The logical volumes defined in `bosinst.data`, together require more than 32 GB.
- D. The `PP_SIZE` in `bosinst.data` value would make the logical volumes > 32 GB combined.