

HP

Exam HP0-022

Version: 3.0

[Total Questions: 67]

Topic 0, A

A

Question No : 1 - (Topic 0)

You configure a VMware HA cluster. During host failure, some of the virtual machines running on this host are not started on the other members of the cluster. What must you verify in your configuration?

- A. if all hosts have access to the storage resources where virtual machines files are located
- B. if the virtual drives of these machines are in persistent mode
- C. if vMotion mechanism is configured on all of the hosts
- D. if these virtual machines have only one virtual processor, as HA will work only for uniprocessor virtual machines

Question No : 2 - (Topic 0)

Your organization has recently acquired an addition to the IT infrastructure with an existing HP SIM server. Because of the geographical location, both HP SIM servers will be kept to manage the infrastructure for location A and location B. You want to provide redundant event handling so that in the event of one HP SIM Server failing, the other server will service event handling. Which steps must you take to accomplish this? (Select three.)

- A. Create Event Handlers on Server A and B that watch each other, and run a custom task that enables a new Event Handler for the other location's devices when the Central Management Server (CMS) in question is unresponsive.
- B. Create Event Handlers on Server A and B that watch each other, and run a custom task that removes the Event Handler for the other location's devices when the CMS comes back online.
- C. Create an Event Handler cluster incorporating Server A and Server B as cluster nodes.
- D. Merge the two CMS databases using the SQL Server Integration Services (SSIS) for SQL 2005.
- E. Create two Event Collections using the Customize Lists option.

Question No : 3 - (Topic 0)

What can you do to decrease oversubscription of a Virtual Connect (VC) Fibre Channel uplink?

- A. Adjust the speed of the mezzanine cards.
- B. Make sure the mezzanine cards use point-to-point or fabric protocols.

- C. Modify the login distribution of the VC SAN fabric.
- D. Add more active ports.

Question No : 4 - (Topic 0)

Why must you use Converged Enhanced Ethernet when using Fibre Channel over Ethernet (FCoE)?

- A. FCoE is a layer 2 protocol and does not support the use of TCP.
- B. FCoE is a layer 2 protocol and does not support the use of IP.
- C. FCoE is a layer 3 protocol and does not support the use of TCP.
- D. FCoE is a layer 3 protocol and does not support the use of IP.

Question No : 5 - (Topic 0)

The HP Virtual Connect FlexFabric 10Gb/24 port module is in Ethernet mode. Match each port status with the correct color indicator. Port Status (place here) (place here) (place here) (place here) (place here) (place here) Port is configured and operating as an uplink port connected to a data center network. Port is operating as a stacking link interconnecting Virtual Connect Modules. Ethernet SFP module is invalid. Unconfigured Port Located (PID) Port is configured as a mirror port. Color of Port Status Indicator Purple Flashing Green Off Amber Flashing Blue Amber pnl1source-1 pnl2source-1 pnl3source-1 pnl4source-1 pnl5source-1 pnl6source-1

Question No : 6 - (Topic 0)

Click on an active logical server. (There is more than one correct answer.)

Question No : 7 - (Topic 0)

Which Virtual Connect Support Utility (VCSU) option provides information about the Virtual Connect module's status?

- A. Showtech
- B. Debug

- C. Diag
- D. Healthcheck

Question No : 8 - (Topic 0)

Click the Exhibit button. Based on the enclosure power information, what is best action plan in addressing the surge in power utilization?

- A. Implement power capping.
- B. Shut down all redundant hosts that are not required.
- C. Disable automation migration.
- D. Manually initiate site failover recovery.

Question No : 9 - (Topic 0)

When using Insight Control Performance Management and viewing a server availability report, what does %Major indicate?

- A. percentage of time that a server is down and unavailable for monitoring
- B. percentage of overall performance that might be approaching a bottleneck condition
- C. percentage of overall performance that is in a bottleneck condition
- D. percentage of overall performance that is satisfactory with no impending or existing bottleneck condition

Question No : 10 - (Topic 0)

Match the features with the correct HP Converged Infrastructure storage product. (One feature will not be used.) Products (place here) (place here) (place here) HP StorageWorks P4000 HP StorageWorks X9000 HP StorageWorks EVA4400 Features Extreme NAS scaleout Network Raid Split-path architecture Dynamic Capacity Management Software pnl1 source-1 pnl2 source-1 pnl3 source-1 pnl4 source-1

Question No : 11 - (Topic 0)

One of your customer's HP-UX virtual servers is not responding to HP Insight Capacity Advisor data collection requests. Which systems management technology should you