

HP

Exam HP0-Y22

Implementing HP ProCurve MultiService

Version: 5.0

[Total Questions: 68]

Topic 0, A

A

Question No : 1 - (Topic 0)

You have been asked by your customer to create a wireless network in a public area with centralized user authentication. Given the following choices, which authentication method would you choose to implement?

- A. 802.1X authentication
- B. MAC authentication
- C. Web authentication
- D. WEP authentication

Answer: C**Question No : 2 - (Topic 0)**

What are the key features of ProCurve Guest Management Software (formerly VMT)? (Select two.)

- A. the ability to create user logo designs
- B. the ability to perform batch creation of user accounts
- C. the ability to print X.509 certificates
- D. the ability to manage a visitor's account on MSM controllers
- E. the ability to import special programs for customer use

Answer: B,D**Question No : 3 - (Topic 0)**

The MSM730 has 4 Ethernet ports; one for the LAN and another for the Internet. What is the function of the other two Ethernet ports?

- A. CLI access
- B. client connectivity
- C. reserved for future expansion
- D. uplinks

Answer: C

Question No : 4 - (Topic 0)

ProCurve's RF Planner is made specifically for which operating system?

- A. Linux
- B. MAC OS
- C. Microsoft Windows
- D. Sun Microsystems Solaris

Answer: C

Question No : 5 - (Topic 0)

If a DHCP server does not exist on a network, the Ethernet port on an autonomous mode MSM Access Point would be assigned a default IP address of 192.168.1.1. Given this information, which statement is correct?

- A. An internal DHCP server in the MSM Access Point can be configured to assign any appropriate IP Address to the port.
- B. An internal dip switch can be configured to change the default IP address of the Ethernet port.
- C. An autonomous mode MSM Access Point can be ordered with the option of a different Default IP Address that could be assigned to its Ethernet port.
- D. Without an external DHCP server, the port will always remain at 192.168.1.1.

Answer: D

Question No : 6 - (Topic 0)

How many Virtual Service Communities (VSCs) does the M110 support?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: B

Question No : 7 - (Topic 0)

How does a client associated to an MSM Access Point receive its DHCP IP Address?

- A. from either the AP's internal DHCP server or an external DHCP server
- B. it cannot receive a DHCP IP Address and a static IP Address is required
- C. through an external DHCP server
- D. with the AP's internal DHCP server

Answer: C

Question No : 8 - (Topic 0)

On the MSM710, PoE can power the device from which port?

- A. port 1
- B. Internet port
- C. LAN port
- D. only as a backup to the direct DC power adapter

Answer: C

Question No : 9 - (Topic 0)

Which 802.11n frequency ranges are supported on the MSM422? (Select two.)

- A. 2.4 GHz
- B. 5 GHz
- C. 20 MHz
- D. 72 MHz
- E. 105.7 MHz

Answer: A,B

Question No : 10 - (Topic 0)

What are the characteristics of the MSM422?

- A. a/b/g/n, single radio
- B. a/b/g/n, triple radio, integrated AP/Controller
- C. a/b/g/n, dual radio, mixed radios
- D. a/b/g, dual radio, mixed radios