

# HP

## Exam HP0-Y26

Version: 3.0

[ Total Questions: 69 ]

**Topic 0, A**

A

**Question No : 1 - (Topic 0)**

You must implement an SNMPv2c solution that will use standard SNMP-Set messages to configure HP switches. Which property must match on the SNMP server and the switches?

- A. manager password
- B. read-only community string
- C. shared secret
- D. read-write community string

**Question No : 2 - (Topic 0)**

On an HP A12500 switch, which type of port can support only one untagged VLAN and multiple 802.1Q VLANs?

- A. hybrid
- B. access
- C. aggregated
- D. trunk

**Question No : 3 - (Topic 0)**

Which view is indicated by the following prompt on an HP A7500 switch?[A7500]

- A. system
- B. manager
- C. user
- D. admin

**Question No : 4 - (Topic 0)**

Click the Exhibit button.What must you do to update the software on the switch shown in the exhibit to version K.14.65?

- A. Copy the new software to the primary flash area and the switch will immediately begin

using the new software.

- B.** Copy the new software to either flash area. Issue the boot system flash command specifying the area holding the new software.
- C.** Copy the new software to the secondary flash area and the switch will immediately begin using the new software.
- D.** Copy the new software to both flash areas and enter the image update command.

**Question No : 5 - (Topic 0)**

What is the relationship between the primary and secondary flash areas of an HP E8206 zl switch?

- A.** The primary area contains the switch's operating system. The secondary area contains the configuration files.
- B.** The primary area contains the switch's operating system, which is automatically copied to the secondary area whenever it is upgraded.
- C.** The primary and secondary images are managed independently, enabling the switch to be started using either image.
- D.** The primary area contains the most recent software version. The secondary area always holds an earlier version as a backup.

**Question No : 6 - (Topic 0)**

In HP PCM+, which privilege is only available to users with the Administrator profile?

- A.** manage all devices
- B.** manage software updates
- C.** manage agents
- D.** manage users

**Question No : 7 - (Topic 0)**

At a customer site, you enter the following command into the CLI of an HP A-Series switch: `stp bpdu-protection` Which BPDUs will the switch discard?

- A.** BPDUs from switches running legacy STP
- B.** BPDUs from switches running PVST+
- C.** BPDUs received by edge ports
- D.** BPDUs from outside its MST region

**Question No : 8 - (Topic 0)**

What is the default status of LLDP on an HP E5400 zl Series switch?

- A. enabled for VLAN 1
- B. enabled globally
- C. enabled for ports that receive LLDP advertisements
- D. disabled

**Question No : 9 - (Topic 0)**

Click the Exhibit button. The two switches in the exhibit are directly connected and have been pre-configured for MSTP. When Spanning Tree is enabled on the switches, how will they converge?

- A. The switches will not be able to exchange BPDUs.
- B. E5406 will become Root Bridge for both instances.
- C. The switches will be in different MST regions.
- D. E3500 will become the Root Bridge for both instances.

**Question No : 10 - (Topic 0)**

Click the Exhibit button. You have defined VLAN 5 and VLAN 6 on an HP E5406 zl switch. You have added four ports to each VLAN as untagged members. All other switch settings are at defaults. What must you do to enable communications between hosts in the two VLANs?

- A. Define a VLAN 1 IP address.
- B. Enable IP routing globally.
- C. Define a default gateway for the switch.
- D. Remove all eight ports from the default VLAN.

**Question No : 11 - (Topic 0)**

Match each A-Series router with its description. RouterDescription(place here)(place here)(place here)ideal as a core router for a medium to small enterprise10G Core router