

HP

Exam HP2-Z08

Migrating to 3Com/H3C Routing and Switching

Version: 6.0

[Total Questions: 79]

Question No : 1

Which switch family runs the Comware V3 operating system?

- A. S7900E
- B. S5820X
- C. S5500-EI
- D. S3600-EI

Answer: D

Question No : 2

On Comware V5 products, which plane supports user authentication, connection management, and VPN?

- A. Service Control Plane
- B. System Management Plane
- C. Data Forwarding Plane
- D. General Control Plane

Answer: D

Question No : 3

A customer requires IPSec encryption performance of 24 Gbps. Which member of the SR6600 family will meet this need?

- A. SR6608
- B. SR6602
- C. SR6604
- D. SR6616

Answer: D

Question No : 4

Which MSR Series routers feature two Gigabit Ethernet Combo fixed interfaces? (Select two.)

- A. MSR 30-40
- B. MSR 50-40
- C. MSR 30-20
- D. MSR 20-40
- E. MSR 20-20

Answer: A,B

Question No : 5

Which upgrade method enables an administrator to upload a new application file to an MSR Series router located in a remote site?

- A. TFTP/FTP
- B. USB flash drive
- C. Boot Menu
- D. Xmodem

Answer: A

Question No : 6

You must clear the startup configuration of an H3C router. Which CLI view will enable you to enter the rest saved-configuration command?

- A. system view
- B. user view
- C. configuration view
- D. local user view

Answer: B

Question No : 7

Which command enables the administrator of an H3C router to enter the OSPF view?

- A. [router] ospf-view
- B. [router] ospf
- C. <router> ospf
- D. <router> ospf-view

Answer: B

Question No : 8

Refer to the exhibit below.

```
system-view
telnet server enable
user-interface vty 0 4
 authentication-mode password
 protocol inbound telnet
 user privilege 1
```

Given this configuration on an MSR Series router, which command is required to enable administrator level privileges?

- A. super password level 3 [simple |cipher] password
- B. privilege 3 password [simple|cipher] password
- C. set administrator level password [simple|cipher] password
- D. local-user admin1 level 3

Answer: A

Question No : 9

Which management interface is available for the initial setup of an MSR Series router?

- A. SSH
- B. console
- C. Telnet
- D. SNMP

Answer: B

Question No : 10

Refer to the exhibit below.

```
GigabitEthernet1/0/1 current state: UP
.
.
.
The Maximum Frame Length is 1522
Broadcast MAX-pps: 3000
Unicast MAX-ratio: 100%
Multicast MAX-ratio: 100%
Forbid jumbo frame to pass
PVID: 202
Mdi type: auto
Link delay is 0(sec)
Port link-type: trunk
  VLAN passing  : 1(default vlan), 200
  VLAN permitted: 1(default vlan), 200-201
  Trunk port encapsulation: IEEE 802.1q
.
.
.
```

Which action will the switch take when an untagged packet is received on port GigabitEthernet 1/0/1?

- A. Place the packet on VLAN 200.
- B. Discard the packet.
- C. Place the packet on VLAN 202.
- D. Place the packet on VLAN 1.

Answer: C

Question No : 11

Refer to the exhibit below.

```

system-view
interface Gig 1/0/23
port link-type trunk
port trunk permit vlan 13 14
port trunk pvid vlan 15
  
```


Which statement describes the VLAN configuration of port GigabitEthernet 1/0/23 shown in the exhibit?

- A. The interface will be tagged on VLAN 1.
- B. Incoming packets tagged for VLAN 1 will be dropped.
- C. Untagged packets will be placed on VLAN 1.
- D. The interface will be tagged on VLAN 15.

Answer: C

Question No : 12

Refer to the exhibit below.



You must configure switches SW-A and SW-B so that interface G 1/0/1 on both switches will forward traffic within VLAN 10 and VLAN 20 while discarding all other traffic. Which

configuration commands will accomplish this goal?

- A. port link-type hybrid
port hybrid pvid 10 20
- B. port link-type access
- C. port link-type trunk
port trunk permit 10 to 20
- D. port link-type trunk
port trunk permit 10 20

Answer: D

Question No : 13

On Comware V5 switches, what is the default load-balancing behavior for LACP?

- A. For routed packets, the load-balancing algorithm is performed on the destination IP address only.
- B. For bridged frames, the load-balancing algorithm is performed on the source and destination MAC address.
- C. For bridged frames, the load-balancing algorithm is performed on the destination MAC address only.
- D. For bridged frames, the load-balancing algorithm is performed on the source MAC address only.

Answer: C

Question No : 14

You must configure several ports on an H3C switch to support protocol-based VLANs. Which VLAN port type should be used on these ports?

- A. Trunk
- B. Aggregated
- C. Access
- D. Hybrid

Answer: D