

JN0-130

JN0-130
Juniper Networks Certified Internet Specialist
(JNCIS-E)

Version 3.1

JN0-130

Contents

Topic 1, Volume A (75 Questions).....	3
Topic 2, Volume B (53 Questions).....	39
Total number of questions = 128	

JN0-130

Topic 1, Volume A (75 Questions)

QUESTION NO: 1

What are two purposes of the RSVP signaling protocol when configuring MPLS Label-Switched Paths (LSPs)? (Choose two.)

- A. to perform a label push operation
- B. to track the status of signaled LSPs
- C. to perform longest-match route lookups
- D. to reserve resources, such as labels and path information

Answer: B,D

QUESTION NO: 2

A Bridged 1483 network is grouping all DSL users into a single logical subnet. Which configuration command prevents the end users from directly communicating with each other?

- A. no ip arp
- B. no ip proxy-arp
- C. restrict ip arp
- D. restrict ip proxy-arp

Answer: B

QUESTION NO: 3

Which three BGP attributes are always communicated in a BGP update packet? (Choose three.)

JN0-130

- A. MED
- B. Origin
- C. AS Path
- D. Next Hop
- E. Aggregator

Answer: B,C,D

QUESTION NO: 4

What is the default Quality of Service traffic class used by the ERX Edge Router?

- A. bronze forwarding
- B. assured forwarding
- C. expedited forwarding
- D. best effort forwarding

Answer: D

QUESTION NO: 5

When configuring an explicit path, what does the next-address entry identify?

- A. the tunnel end point
- B. the tunnel start point
- C. a specific node to be traversed

JN0-130

D. the node prior to the tunnel end point

Answer: A

QUESTION NO: 6

On a 3-port CT3 card, how many HDLC controllers does each port support?

A. 64

B. 128

C. 512

D. 1024

Answer: B

QUESTION NO: 7

Which type of hop in an ERO must be directly connected to the previous hop?

A. full

B. strict

C. loose

D. partial

Answer: B

QUESTION NO: 8

JN0-130

Which configuration component is required to allow a PPP over ATM client to connect to one virtual router for a particular session and to a different virtual router for another session?

- A. profile
- B. domain map
- C. IP access-route
- D. static IP addressing

Answer: A

QUESTION NO: 9

Which IS-IS authentication method is supported on the ERX Edge Router?

- A. simple password
- B. HMAC message digest 5
- C. Password Authentication Protocol
- D. Challenge Handshake Authentication Protocol

Answer: B

QUESTION NO: 10

You would like to configure an Ethernet interface with the following characteristics: ?

Fast Ethernet port 3/2 ?

192.168.1.1/24 ? VLAN 21 ?

Description "SNMP-Mgmt"

JN0-130

Which set of configuration commands accurately completes this task?

A. interface fast 3/2

description SNMP-Mgmt

encap vlan

interface fast 3/2.21

vlan id 21

ip address 192.168.1.1 255.255.255.0

B. interface fast 3/2

encap vlan

interface fast 3/2.21

vlan id 21

ip address 192.168.1.1 255.255.255.0

description SNMP-Mgmt

C. interface fast 3/2

encap vlan

description SNMP-Mgmt

interface fast 3/2.21

vlan id 21

ip address 192.168.1.1 255.255.255.0

D. interface fast 3/2

encap vlan

vlan id 21

interface fast 3/2.21

JN0-130

ip address 192.168.1.1 255.255.255.0

description SNMP-Mgmt

Answer: B

QUESTION NO: 11

What is true about a Bypass Tunnel in MPLS Fast Reroute?

- A. Only configured on the egress router.
- B. Only configured on the ingress router.
- C. Is pre-signalled to reduce packet loss.
- D. Must intersect the primary LSP at two locations.

Answer: D

QUESTION NO: 12

Which two statements are correct regarding MPLS LSP establishment methods? (Choose two.)

- A. LDP uses Down Stream On Demand.
- B. RSVP uses Down Stream On Demand.
- C. LDP uses Down Stream Unsolicited.
- D. RSVP uses Down Stream Unsolicited.

Answer: B,C

JN0-130

QUESTION NO: 13

What is the default value of the IS-IS lsp-refresh-interval command?

- A. 60 seconds
- B. 5 minutes
- C. 15 minutes
- D. 30 minutes

Answer: C

QUESTION NO: 14

Where is OSPF authentication configured on the ERX Edge Router?

- A. interface
- B. OSPF area
- C. virtual router
- D. OSPF process

Answer: A

QUESTION NO: 15

Which statement describes queue and buffer management in the E-series router?

- A. Buffer memory is managed dynamically in the I/O module.
- B. Buffer memory is managed dynamically in the switch fabric.

JN0-130

- C. Buffer memory is managed dynamically on egress line modules.
- D. Buffer memory is managed dynamically on ingress line modules.

Answer: C

QUESTION NO: 16

What are three valid LDP message types? (Choose three.)

- A. peer discovery
- B. label distribution
- C. path initialization
- D. session management
- E. connection establishment

Answer: A,B,D

QUESTION NO: 17

What is a Label-Switched Path?

- A. a traffic engineered path
- B. another name for a Frame Relay PVC
- C. a bidirectional path through a network
- D. a unidirectional path through a network

Answer: D