

Paloalto Networks

Exam PCNSE7

Palo Alto Networks Certified Network Security Engineer

Version: 8.3

[Total Questions: 60]

Question No : 1

A host attached to Ethernet 1/4 cannot ping the default gateway. The widget on the dashboard shows Ethernet 1/1 and Ethernet 1/4 to be green. The IP address of Ethernet 1/1 is 192.168.1.7 and the IP address of Ethernet 1/4 is 10.1.1.7. The default gateway is attached to Ethernet 1/1. A default route is properly configured.

What can be the cause of this problem?

- A. No Zone has been configured on Ethernet 1/4.**
- B. Interface Ethernet 1/1 is in Virtual Wire Mode.
- C. DNS has not been properly configured on the firewall.
- D. DNS has not been properly configured on the host.

Answer: A

Question No : 2

Which two mechanisms help prevent a split brain scenario an Active/Passive High Availability (HA) pair? (Choose two)

- A. Configure the management interface as HA3 Backup
- B. Configure Ethernet 1/1 as HA1 Backup
- C. Configure Ethernet 1/1 as HA2 Backup
- C. Configure the management interface as HA2 Backup
- D. Configure the management interface as HA1 Backup
- E. Configure ethernet1/1 as HA3 Backup

Answer: B,E

Question No : 3

Company.com has an in-house application that the Palo Alto Networks device doesn't identify correctly. A Threat Management Team member has mentioned that this in-house application is very sensitive and all traffic being identified needs to be inspected by the Content-ID engine.

Which method should company.com use to immediately address this traffic on a Palo Alto Networks device?

Paloalto Networks PCNSE7 : Practice Test

- A.** Create a custom Application without signatures, then create an Application Override policy that includes the source, Destination, Destination Port/Protocol and Custom Application of the traffic.
- B.** Wait until an official Application signature is provided from Palo Alto Networks.
- C.** Modify the session timer settings on the closest referenced application to meet the needs of the in-house application
- D.** Create a Custom Application with signatures matching unique identifiers of the in-house application traffic

Answer: A

Question No : 4

A company has a policy that denies all applications it classifies as bad and permits only application it classifies as good. The firewall administrator created the following security policy on the company's firewall.

	Name	Source			Destination		Application	Service	Action	Profile	Options
		Zone	Address	User	Zone	Address					
1	rule1	Trust-L3	any	any	UnTrust-L3	any	Known Good	application-default	Allow	Log	Log
2	rule2	Trust-L3	any	any	UnTrust-L3	any	Known Bad	any	Deny	none	Log
3	rule3	Trust-L3	any	any	UnTrust-L3	any	any	any	Deny	none	Log

Which interface configuration will accept specific VLAN IDs?

Which two benefits are gained from having both rule 2 and rule 3 presents? (choose two)

- A.** A report can be created that identifies unclassified traffic on the network.
- B.** Different security profiles can be applied to traffic matching rules 2 and 3.
- C.** Rule 2 and 3 apply to traffic on different ports.
- D.** Separate Log Forwarding profiles can be applied to rules 2 and 3.

Answer: A,B

Question No : 5

A network security engineer has been asked to analyze Wildfire activity. However, the Wildfire Submissions item is not visible from the Monitor tab.

What could cause this condition?

- A. The firewall does not have an active WildFire subscription.
- B. The engineer's account does not have permission to view WildFire Submissions.
- C. A policy is blocking WildFire Submission traffic.
- D. Though WildFire is working, there are currently no WildFire Submissions log entries.

Answer: A

Question No : 6

Support for which authentication method was added in PAN-OS 7.0?

- A. RADIUS
- B. LDAP
- C. Diameter
- D. TACACS+

Answer: D

Question No : 7

A network security engineer is asked to perform a Return Merchandise Authorization (RMA) on a firewall

Which part of files needs to be imported back into the replacement firewall that is using Panorama?

- A. Device state and license files
- B. Configuration and serial number files
- C. Configuration and statistics files
- D. Configuration and Large Scale VPN (LSVPN) setups file

Answer: B

Question No : 8

A network administrator uses Panorama to push security polices to managed firewalls at branch offices. Which policy type should be configured on Panorama if the administrators at the branch office sites to override these products?

- A. Pre Rules
- B. Post Rules
- C. Explicit Rules
- D. Implicit Rules

Answer: A

Question No : 9

ION NO: 40

Palo Alto Networks maintains a dynamic database of malicious domains.

Which two Security Platform components use this database to prevent threats? (Choose two)

- A. Brute-force signatures
- B. BrightCloud Url Filtering
- C. **PAN-DB URL Filtering**
- D. **DNS-based command-and-control signatures**

Answer: C,D

Question No : 10

Which two statements are correct for the out-of-box configuration for Palo Alto Networks NGFWs? (Choose two)

- A. The devices are pre-configured with a virtual wire pair out the first two interfaces.
- B. The devices are licensed and ready for deployment.
- C. **The management interface has an IP address of 192.168.1.1 and allows SSH and HTTPS connections.**
- D. **A default bidirectional rule is configured that allows Untrust zone traffic to go to the Trust zone.**
- E. The interface are pingable.

Answer: B,C

Question No : 11